

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number
WO 2005/092474 A1

(51) International Patent Classification⁷: **B01D 39/20**

(21) International Application Number:
PCT/GB2004/001271

(22) International Filing Date: 23 March 2004 (23.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **DYTECH CORPORATION LIMITED** [GB/GB]; Stubble Lane, Dronfield, Sheffield, South Yorkshire S18 1LS (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SAMBROOK, Rodney, Martin** [GB/GB]; 15 Pine View, Ashgate, Chesterfield S40 4DN (GB).

(74) Agent: **HLBB LIMITED**; 1 Hagley Road, Edgbaston, Birmingham B16 8TG (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FILTER MATERIAL



1



2

(57) Abstract: A method of treating a process stream by catalysis, which method comprises passing the process stream through a chemical reactor containing catalytic material and including the step of passing the process stream through a layer of filter material located in the reactor, the layer comprising shaped porous bodies of ceramic material, the porosity being from about 65% to about 90%, the pores being defined by struts and windows.

WO 2005/092474 A1